

## Attachment A

Custom Configuration 817-BBBB - 500 -  
Wyse 5070 thin client, CTO 210-ARLC - 500 -  
Intel Celeron J4105 (4 Cores/4MB/4T/up to 2.5GHz/10W) supports  
Wyse ThinOS/ThinOS+PCoIP/Windows IoT 338-BOBO - 500 -  
Wyse ThinOS Firmware Access 619-ANNK - 500 -  
PCoIP enabled Wyse ThinOS 9.X 619-APOH - 500 -  
4GB 1x4GB, 2400MHz DDR4 Memory 370-AFBG - 500 -  
32G eMMC Included in Chassis 400-AWEB - 500 -  
No Additional Hard Drive 401-AANH - 500 -  
No Wireless LAN Card (no WiFi enablement) 555-BBFO - 500 -  
None Required 817-BBBP - 500 -  
None Required 817-BBBP - 500 -  
Wyse 5070 thin client, Intel Celeron Processor J4105, 32G eMMC,  
GSA 329-BDQI - 500 -  
Dell Wired Keyboard KB216 Black (English) 580-ADOY - 500 -  
Dell Optical Mouse-MS116 Black 570-AATE - 500 -  
US Power Cord 450-ACSP - 500 -  
65W AC Adapter 492-BCHL - 500 -  
English and French, Shipping Docs 340-APZS - 500 -  
Tech Sheet (English, French, Spanish, Brazilian Portuguese) 340-BYYL - 500 -  
Energy Star Compliant 340-AAPZ - 500 -  
ENERGY STAR Qualified 389-BKKG - 500 -  
No UPC Label 389-BCGW - 500 -  
Shipping Material for System 340-BZFG - 500 -  
Ship Material, Shuttle, E-dock 750-AACL - 500 -  
Intel(R) Celeron(R) Label 340-AQVB - 500 -  
Regulatory Label with 65W AC Adapter 389-DOSY - 500 -  
System Ship Info 640-BBJB - 500 -  
Wyse Software Driver for Thin OS/Linux 658-BDSS - 500 -  
Dell Limited Hardware Warranty Extended Year(s) 805-0837 - 500 -  
Dell Limited Hardware Warranty 805-0838 - 500 -  
ProSupport: 7x24 Technical Support, 2 Years Extended 805-0851 - 500 -  
ProSupport: 7x24 Technical Support, Initial Year 805-0856 - 500 -  
ProSupport: Next Business Day Onsite Service After Remote  
Diagnosis, 2 Years Extended 815-7785 - 500 -  
ProSupport: Next Business Day Onsite Service After Remote  
Diagnosis Initial Year 815-7788 - 500 -  
Thank you choosing Dell ProSupport. For tech support, visit  
[//support.dell.com/ProSupport](https://support.dell.com/ProSupport) 989-3449 - 500 -  
Vertical stand for Dell Wyse 5070 thin client 452-BDBT - 500 -  
NO ADAPTER 470-AAJL - 500 -